

Description "Sterling"		Max. sash Weight (kg)	Min. sash HHS (mm)	Max. sash HHS (mm)	Min. sash LHS (mm)	Max. sash LHS (mm)	sash fixing				Frame fixing				
							"A"	"B"	"C"	"D"	"E"	"F"	"G"	"H"	"I"
Top Hung	SPT10	40	400	635	-	-	40.8	-	-	165.1	-	177.8	-	218.2	-
	SPT12	50	636	787	-	-	65.0	-	-	190.1	-	212.7	-	269.0	-
	SPT16/SPT16W	65	788	1090	-	-	118.4	-	-	241.2	215.7	304.0	-	370.6	-
	SPT22	100	1091	1500	-	-	65.0	-	203.2	317.4	251.3	418.3	-	523.0	-
	SPT22W	100	1501	2000	-	-	80.0	-	235.8	350.0	-	295.4	-	526.5	-
	SPT26	180	2001	2200	-	-	65.0	189.0	314.4	383.9	161.4	292.4	584.5	638.5	676.8
Side Hung	SPS10	38	-	-	400	660	34.0	-	-	165.1	-	177.8	-	218.2	-
	SPS16	55	-	-	450	838	65.0	-	-	241.2	-	212.9	-	370.6	-

